

## **Landing Valve**

**Model: FIS281 (Female X Female)**


Landing Valve

Version 1.03  
July 2025 release

# Landing Valve

## Model: FIS281

### (Female X Female)



## Technical Features

Used with a Fire Hose Rack Assembly or as a Fire Department outlet connection

### DOUBLE FEMALE

Standard Equipment	Female NPT inlet and outlet Forged brass valve Red hand wheel
Optional Finishes	PB - Polished Brass RC - Rough Chrome Plated PC - Polished Chrome Plated
NYFD	2 ½" FNPT x FNPT 1 ½" FNPT x FNPT
Maximum Working Pressure	300 PSI
Options	Male adaptor available

## Valve Material List

No	Description	Material
1	Body	ASTM B283 C37700
2	Nut	ASTM B283 C37700
3	Washer	304
4	Seat Seal	EPDM (A70)
5	Holder	C37700
6	Set Screw	304
7	Lock Nut	ASTM B283 C37700
8	O-Ring	EPDM (A70)
9	Bonnet	ASTM B283 C37700
10	Stem	ASTM B283 C37700
11	Lock Nut	ASTM B283 C37700
12	O-Ring	EPDM (A70)
13	Handle Wheel	ZL 102
14	Wheel Washer	304
15	Wheel Nut	ASTM B283 C37700

## Dimensions

Part No.	Size	A	B	C	D	E
FIS281-040FF	1 ½" x 1 ½"	100	50	66	119	145
FIS281-065FF	2 ½" x 2 ½"	127	68	84	157	200



Gate 2, Aljada Logistics Area,  
Behind Arada Project Management  
Office, Near Airport Road,  
Muweilah, 22436, Sharjah

[rhinotek.ae](http://rhinotek.ae)